# Honeywell

GENERAL PURPOSE HANDHELD

# Voyager 1350g Affordable 2D Area Imager Scanner

Voyager 1350g is designed for a large variety of applications, Voyager™ 1350g is an area imager scanner that incorporates the latest generation technology in a compact and easy to use form factor.

## Overview



Voyager 1350g is featuring an ideal balance of performance, ergonomics and price, It is a cost-effective solution for a wide variety of data capture applications. Voyager 1350G can be used in government departments for personnel registration, hotel registrations, theater ticket checking, and even hospitals and schools that need a quick and fast scan, for hospitality and admission purposes.

Voyager 1350g supports all popular 1D and 2D barcodes, as well as image capture capability. Incorporating latest technology from Honeywell, Voyager 1350G is easy to install and configure, the user being able to quickly select configurations and personalize the scanning experience. Voyager 1350G is compatible with Honeywell's advanced EZConfig and support all common POS drivers, being ready to adapt to different applications and requirements.

# Specifications

## **FEATURES**

## **Features**

• Honeywell Operational Intelligence

## **DIMENSIONS**

## **Overall Dimensions**

• 72.5mm×125mm×154mm (2.85 in \*4.92 in \*6.06 in)

## **SCANNING SPECIFICATIONS**

## **Decode Capability**

• 1D/2D

#### **Scan Pattern**

Array

#### **Motion Tolerance**

• 75 cm/s

#### **Number of Scans**

• usb

## **Brightness**

• 0 - 100000 lux

## **Scanning Range**

• 35mm-430mm(13mil UPC-A)

## **Depth of Field**

• 35mm-430mm(13mil UPC-A)

## **NETWORK**

## **Bluetooth Specifications**

• 1.2m

## Bluetooth

• 35mm-430mm(13mil UPC-A)

## **HARDWARE**

## **Host System Interface**

• USB, RS-232

## **Aimer Type**

• Area Image

## **Engine Type**

• 2D

## Wireless

Corded

## **ELECTRICAL**

## **Smart Battery**

• N/A

## **Battery Types**

• 1D/2D

## **ENVIRONMENTAL**

#### **Storage Temperature Range**

• -40°C to 60°C (-40°F to 140°F)

## **Operating Humidity**

• 0% to 95% relative humidity

## **STANDARDS & APPROVALS**

#### **Protection Ratings**

• IP40

## **Drop Specifications**

• 1.2m

## **Tumble Specifications**

• 250, 0.5 m (1.6 ft tumbles)

## **OTHERS**

#### **Form Factor**

• Gun shape

## **Application**

• Point of Sale ,Retail

## For Use With

• EZ Config Tool

## **Operating Power**

• 2 W

## **Battery Capacity**

• 0 - 100000 lux

## Input Voltage

• 4 - 5.5 V DC

## **Operating Temperature**

• 0 - 50 °C32 - 122 °F

## **Warranty Duration**

3 years

## **Power Connector Type**

• usb